





## **Grade 80 Eye Safety Hook**

Eye safety hook locks when a load is applied to prevent the release of chains and lifting slings.

## **Applications**

- Use with Grade 80 lifting components
- · Lifting with chains and synthetic slings

**Material** 



**Finish** 





## **Features**

- · Conforms to AS 3776
- 100% magnaflux crack detection
- Safety hook prevents components from releasing if line becomes slack
- · Back lever releases hook




Part	QFind	Size	WLL	BL	Dimensions				
		(mm)	(tonne)	(tonne)	B (mm)	<b>D</b> (mm)	K (mm)	H (mm)	L (mm)
ULHK08PSE-06	HSE6	6	1.12	4.48	28.0	22	110.5	20	141.0
ULHK08PSE-08	HSE8	8	2.00	8.00	35.0	25	136.0	24	172.0
ULHK08PSE-10	HSE10	10	3.15	12.60	45.0	32	169.0	28	210.0
ULHK08PSE-13	HSE13	13	5.30	21.20	54.0	40	208.0	41	265.0
ULHK08PSE-16	HSE16	16	8.00	32.00	60.5	50	245.5	50	325.0
ULHK08PSE-20	HSE20	20	12.50	50.00	74.5	61	290.0	62	378.0
ULHK08PSE-22	HSE22	22	15.00	60.00	80.0	72	320.0	65	416.0
ULHK08PSE-26	HSE26	26	21.20	84.80	99.0	80	362.0	74	472.0
ULHK08PSE-32	HSE32	32	31.50	126.00	146.0	105	471.5	96	612.5



## **MARKINGS:**

- CE (European Conformity)
- WLL (Working Load Limit)
- Trace Code (linked to certificate online)
- Manufacturer's mark





Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document.

